

# Panasonic

# AG-UX90

Memory Card Camera Recorder  
(50 Hz Model)

Scheduled for release in November 2016

\*The microphone shown in the photo is an optional accessory.

**4K (UHD) / FHD Camcorder with a Wide-Angle 24.5mm\*,  
15x Optical Zoom Lens and 1.0-Type MOS Sensor**



**UX SERIES**  
FOR PROFESSIONAL 4K SHOOTING



\*35mm film camera equivalent in FHD mode. 35.4mm in UHD mode.

# UX SERIES

FOR PROFESSIONAL 4K SHOOTING

Featuring a wide-angle 24.5mm\*<sup>1</sup>, 15x optical zoom lens and 1.0-type MOS sensor, the AG-UX90 records high-quality 4K/FHD images with excellent cost-performance.

Panasonic introduces the 4K camcorder UX series to meet professional 4K video production needs.

The AG-UX90 is the "UX standard model" for easy, high-quality 4K/FHD recording.

It is equipped with a newly designed compact lens featuring a wide 24.5mm angle\*<sup>1</sup> and 15x optical zoom. Its Optical Image Stabilizer (O.I.S.), intelligent AF function, and Manual Three Rings are ideal for professional camera work.

The AG-UX90 is equipped with a 1.0-type high-sensitivity MOS sensor. It supports UHD 25p and FHD 50p/25p multi-format recording. In addition to 4K (UHD) high resolution, it provides high-quality FHD recording at 50 Mbps. Two SD memory card slots enable relay/simultaneous recording.

The AG-UX90 also has a design and operating ease that will feel familiar to professional photographers, and a variety of interfaces, including HDMI output and XLR input. Offering the same level of agility and mobility as a conventional HD handheld camcorder, the AG-UX90 provides powerful support for high-image-quality 4K/HD video production.

## Newly Developed Wide-Angle 24.5mm\*<sup>1</sup> and 15x Optical Zoom LEICA DICOMAR Lens

- **15x Optical Zoom:** The 4-Drive Lens System achieves both high image quality/sensitivity and compactness with a wide-angle 24.5mm\*<sup>1</sup> and 15x optical zoom lens. This speedy zoom provides quick zooming in and out.
- **High-Resolution Intelligent Zoom:** In FHD mode, the i.Zoom function increases the zooming capability to a maximum of 25x while maintaining high resolution. The i.Zoom function seamlessly switches on when the optical zoom limit is reached.
- **Digital Zoom (x2/x5/x10):** The Digital Zoom function activates without any drop in light intensity. Combining the optical zoom and i.Zoom enables maximum zooming of 250x\*<sup>2</sup>.
- **LEICA DICOMAR\*<sup>3</sup> Lens:** This lens has passed the stringent quality standards of Leica Camera AG. A multi-coating process minimizes ghosts and flaring, resulting in especially clear images.

\*1: 35mm film camera equivalent in FHD mode. 35.4mm in UHD mode.

\*2: Using 15x Optical Zoom + i.Zoom + Digital Zoom 10x in FHD mode. The higher the magnification, the greater the image quality degradation.

\*3: Leica is a registered trademark of Leica Microsystems IR GmbH. DICOMAR is a registered trademark of Leica Camera AG. LEICA DICOMAR products are manufactured using Leica-certified measuring instruments and quality assurance systems based on rigorous quality standards approved by Leica Camera AG.

LEICA  
DICOMAR




An image shot on a bus using the wide angle.

## 1.0-Type MOS Sensor for High-Precision, UHD 25p or FHD 50p Recording

- **High-Image-Quality, High-Sensitivity, 1.0-Type 4K MOS Sensor:** The 1.0-type MOS sensor provides an outstanding depth of field and excellent balance between image quality and sensitivity. High-resolution recording is possible in UHD (3840x2160) 25p mode.
- **High-Image-Quality FHD Recording:**


Professional, high-end image recording is possible in FHD (1920x1080) mode with a 50-Mbps bit rate.

- **UHD/FHD/SD Multiformat:** Versatile recording modes can be selected according to resolution, frame rate, bit rate, and file format. (See table below.)



### Recording Format Supported by AG-UX90

	Image Size	Frame Rate	Bit Rate	Compressed Mode	Sound	File Format	
UHD	3840x2160	25.00p	100Mbps	LongGOP	LPCM	MOV or MP4	
HIGH BITRATE FHD	1920x1080	50.00p/25.00p/50.00i	50Mbps	LongGOP	LPCM	MOV or MP4	
		50.00p	25Mbps				
AVCHD	1920x1080	50.00i	21Mbps	LongGOP	AC3	AVCHD	
		50.00i	17Mbps				
		1440x1080	50.00i				5Mbps
		1280x720	50.00p				8Mbps
		720x576	50.00i (16:9/4:3)				9Mbps



## Advanced Optical Image Stabilizer and High-Speed, High-Precision Intelligent AF



- **Advanced Optical Image Stabilizer [UHD/FHD]:** The correction area of the Optical Image Stabilizer (O.I.S.) has been expanded to approximately 900% over the conventional area (as compared to the Panasonic AG-AC160). This provides powerful correction even in unstable shooting situations, such as low-angle or high-angle shots.
- **5-Axis Hybrid Image Stabilizer [FHD]:** In HD shooting modes, by using hand-shake correction that combines the effects of both optical and electronic image stabilization, hand-shake in various directions, including the rotary direction, is detected and corrected.
- **Intelligent Auto Focus:** The Microdrive Focus Unit achieves superior auto focusing with higher-speed tracking and stability even in 4K images. The highest class\*5 of focusing speed, tracking ability, and stability are attained in 4K video cameras.
- **Custom AF Function:** Auto focus operation can be customised by adjusting the AF Speed, AF Sensitivity and AF Area Width. This function enables the AF to operate exactly as intended by the user in accordance with the subject type or application.

\*5: As a camcorder with integrated lens having a 1.0-type sensor. (As of September 2016, according to Panasonic survey.)

## Versatile Manual Functions – Manual Three Rings + Focus Assist

- **Manual Three Rings:** The AG-UX90 features manual three rings for Zoom, Focus and Iris control. These manual controls ensures professional operation.
- **Focus Assist (Expand and Peaking):** Expand (enlargement)\*6 or Peaking (coloured emphasis of focus point) is displayed to assist the user's manual focusing operation.
- **One-Push AF:** This function temporarily activates Auto Focus when shooting in Manual Focus mode, using a "PUSH AUTO" button.
- **Area Function:** Auto Focus is easily possible with just a touch on the LCD panel. You can also change this to Auto Iris and Brightness Display.

\*6: The part to be expanded is designated by touching the screen.



# UX SERIES

FOR PROFESSIONAL 4K SHOOTING




## FHD VFR (Variable Frame Rate) Recording, Double SD Memory Card Slots

- **FHD VFR Recording:** VFR recording can be set in 9 steps from 2 to 50 fps.
- **Unlimited Relay Recording:** By using double SD memory card slots, automatically records continuously from Slot 1 to Slot 2. By changing the SD card, images can be recorded continuously for many hours\*1.
- **Simultaneous Recording:** By using double SD memory card slots, identical data is recorded onto cards in both slots in this dual recording mode.
- **Pre Rec:** This function constantly caches approximately 4 seconds of video and audio data in MOV/MP4 format, or approximately 3 seconds in AVCHD format, prior to Rec Start, so the data can be recovered in case there is a delay in pressing Rec Start.
- **Interval Rec:** Records intermittently based on a set interval time of 1 sec, 10 sec, 1 minute or 2 minutes.
- **Freeze Frame:** Images can be recorded as still images together with audio. This function is convenient when moving the camera to a different location or when shooting a different scene.
- **Time Stamp:** The date and time can be stamped onto recorded images.

\*1: The maximum amount of data that can be recorded over multiple SD cards is 96 GB. Recording will not stop even when the data size exceeds 96 GB.

### Unlimited Relay Recording



### Simultaneous Recording





## Camera Image Adjustment Functions, Including Details and Gamma Modes

- **Skin Detail:** Makes skin colours appear soft and beautiful. Especially effective when recording the person up close.
- **Master Detail:** Adjusts the overall degree of contour enhancement.
- **8-Mode Gamma:** The AG-UX90 is equipped with eight selectable gamma modes, including two Cine-Like Gammas, drawing on technologies developed for the VariCam.

HD NORM:	Suitable for standard HD recording.
SD NORM:	Increased gain in darker areas more than HD (High Definition).
FILMLIKE 1:	Reproduces more gradation in highlight areas than when shooting in HD.
FILMLIKE 2:	Reproduces more gradation in highlight areas than when shooting in FILMLIKE 1.
FILMLIKE 3:	Reproduces more gradation in highlight areas than when shooting in FILMLIKE 2.
CINE-LIKE D:	The Cine-Like mode shifted to prioritize dynamic range.
CINE-LIKE V:	The Cine-Like mode shifted to prioritize contrast.
STILL-LIKE:	Setting to match images captured with still cameras.

- **Scene Files:** Six files preset with picture quality settings are provided as Scene Files (Standard, Shooting under fluorescent lights, Spark, Still like, CINE-LIKE contrast, and CINE-LIKE dynamic range). You can change any of the settings as desired and store one set as a Custom File in the AG-UX90, and up to eight sets on an SD memory card.
- **Other Professional Picture Quality Settings:** Selectable matrix tables including CINE-LIKE mode, V detail, detail coring, chroma level, chroma phase, colour temperature, master pedestal and knee point.



Master Detail OFF \* picture simulated Master Detail ON



## Functions and Designs to Support Professional Camera Work

- **User Buttons:** Any of the 44 functions can be allocated to the User Buttons. There are a total of 13 User Buttons: Nine on the AG-UX90 body, and four on the LCD Touch Panel.
- **Touch-panel LCD and EVF:** The 3.5-type monitor LCD built into the handle section can be pulled out and turned 270 degrees in the vertical direction for use in high-angle, low-angle or selfie shots. The touch panel function can be used for menu setting and area functions. The 0.24-type LCD colour viewfinder is also equipped.
- **ND Filters:** OFF, 1/4, 1/16, 1/64 ND filters built-in.
- **Gain Selector:** Select from -3 dB to 30 dB gain for 3-position (L/M/H) allocation.
- **AWB Selector:** Two-value (A/B) memory and presets (3200/5600/VAR) can be selected. ATW (auto-tracking white balance) function is also equipped.
- **ZEBRA/Marker (Y Level):** Two zebra patterns are integrated, from 50% to 105% in 5% steps. When switched to Marker, the brightness level in the centre of the screen is displayed in percentage.
- **Level Gauge:** Horizontal or vertical tilting of the camcorder can be checked.
- A Safety Zone Marker and Centre Marker can be displayed.

## Professional Interfaces for Smooth System Operation

- **HDMI:** Digital outputs up to UHD 25p and FHD 50p. **HDMI**
- **VIDEO/AUDIO OUT:** Outputs analogue signals for video and audio monitoring.
- **XLR AUDIO IN:** Equipped with two channels of XLR audio input (with switchable 48 V phantom power supply, MIC and LINE), manual audio volume and OSD level meter.
- **Professional Audio Recording:** The AG-UX90 records two high-quality audio channels using either the 16-bit linear PCM system (MOV/MP4) or Dolby Digital system (AVCHD). Other professional features include a 1-kHz test tone output\*2 and headphone output (3.5 mm-diameter stereo mini-jack). **DOLBY DIGITAL**
- **iPad Remote Control:** The AG ROP app for iPad\*3 is available free of charge from the Apple App Store. It enables wireless remote control of the AG-UX90 with installation of a wireless module (optional AJ-WM50 or AJ-WM30). This enables a variety of control operations, including Zoom, Iris, REC Start/Stop, and picture quality settings.
- **Large-Capacity Battery Options:** The AG-VBR59/VBR89G/VBR118G new battery packs offer large capacity and quick charge\*4.

\*2: This output is produced when the colour bar is displayed. The output is 997 Hz.

\*3: iOS 7.1, iOS 8.1, and iOS 9 are supported.

• App Store is a service mark of Apple Inc. Apple, the Apple logo, and iPad are trademarks of Apple Inc., registered in the U.S. and other countries.

\*4: Quick charge is possible only when the AG-BRD50 battery charger is used.



Zebra



\* Pictures simulated.

Marker



Safety Zone Marker

Center Marker


Spirit Level



AG ROP  
Download on the App Store

# UX SERIES

FOR PROFESSIONAL 4K SHOOTING



\*1: Not available in some areas.

\*2: Operation check models: ATOMOS SHOGUN.

## Options

As of September, 2016



**AG-VBR118G** (11,800 mAh)  
**AG-VBR89G** (8,850 mAh)  
**AG-VBR59** (5,900 mAh)  
 Battery Pack



**AG-BRD50**  
 Battery Charger



**VW-VBD58** (5,800 mAh)  
 Battery Pack



**AG-B23**  
 Battery Charger



**AG-MC200G**  
 XLR Microphone



**VW-LED1**  
 LED Video Light



**AJ-WM50/WM30**  
 Wireless Module

\*Not available in some areas



**BT-4LH310**  
 787.4 mm (31 inches) 4K LCD  
 Monitor



**FZ-Y1CG**  
 20-type 4K Business Rugged  
 Toughpad



**RP-SDUE12DVX** (128 GB)  
**RP-SDUE64DVX** (64 GB)  
 SDXC Memory Card

\* For more information, visit the  
 Panasonic website [http://panasonic.net/avc/sdcard/business\\_sd\\_i/lineup\\_UE-DVX.html](http://panasonic.net/avc/sdcard/business_sd_i/lineup_UE-DVX.html)



SD/SDHC/SDXC Memory Card

\* UHS Speed Class 3 (U3) SD  
 memory card is necessary for video  
 recording of 100 Mbps or more.  
 UHS Speed Class 3 (U3) SDXC  
 memory card of 64 GB or more is  
 necessary for video recording of  
 UHD2160/59.94p/50.00p 150 M.

### UX PREMIUM MODEL



## AG-UX180

4K 60p/50p\*1 Camcorder featuring the Industry's  
 Widest Angle 24mm\*2, 20x Optical Zoom  
 and 1.0-type MOS Sensor

\*1: Actual recording is UHD (3840 x 2160) 59.94p/50p.

\*2: Equivalent to 35mm under 4K 24p (aspect ratio of 17:9) Wide  
 angle 24mm is the widest in the industry for a camcorder with  
 integrated lens. (As of September 2016, according to Panasonic  
 survey.)

# Specifications

Tentative, as of September, 2016

<b>General</b>							
Power:	DC 7.28 V (when the battery is used) DC 12 V (when the AC adaptor is used)	System Format:	50 Hz	Recording Format:	MOV, MP4, AVCHD	Recording Mode:	Please see page 1 for the Recording Format table.
Power Consumption:	12.2 W (when the LCD monitor is used)	Recording Time:	Please see below for the Recording Time table.	2 Slot Functions:	Relay, Simultaneous	Still Picture Recording Mode:	JPEG (DCF/Exif2.2)
Operating Temperature:	0 °C to 40 °C (32 °F to 104 °F)	Still Picture Recording:	Motion Picture Playback: 8.3 M: 3840 x 2160 (16:9), 2.1 M: 1920 x 1080 (16:9), 0.9 M: 1280 x 720 (16:9)	<b>Digital Video</b>			
Operating Humidity:	10 % to 80 % (no condensation)	Video Signal for External Output: 8 bit 4:2:2		Recording Video Signal: 8 bit 4:2:0			
Weight:	Body: Approx. 1.9 kg (4.19 lb) (body only, excluding lens hood, battery, and accessories) Shooting: Approx. 2.3 kg (5.07 lb) (including lens hood, battery, and eye cup)	Video Compression Format: MPEG-4 AVC/H.264 High Profile (MOV/MP4/AVCHD)		<b>Digital Audio</b>			
Dimensions:	169 mm (W) x 195 mm (H) x 340 mm (D) (6-21/32 inches x 7-11/16 inches x 13-3/8 inches) (excluding protrusion and eye cup) 169 mm (W) x 195 mm (H) x 382 mm(D) (6-21/32 inches x 7-11/16 inches x 15-1/32 inches) (including eye cup, excluding protrusion)	Sampling Frequency: 48 kHz/16 bit 2 ch		Audio Signal Format: LPCM (MOV/MP4), Dolby Digital (AVCHD)			
<b>Camera Unit</b>		Headroom: 12 dB		<b>Video Input/Output</b>			
Pickup Device:	1.0-type MOS solid state image sensor	VIDEO OUT: VIDEO OUT connector x 1		HDMI: Type A connector x 1, VIERA Link not supported Output format: 2160/25.00p, 1080/50p/25p/50i, 720/50p, 576/50p			
Effective Pixels:	17.78 megapixel: FHD 50.00p/25.00p 8.59 megapixel: UHD 25.00p	Audio Input		Built-in Microphone: Stereo microphone			
Lens:	Optical image stabilizer lens, optical 15x motorized zoom F2.8 to F4.5 (f=8.8 mm to 132 mm) 35 mm equivalent: f=24.5 mm to 367.5 mm: FHD 50.00p/25.00p f=35.4 mm to 531.0 mm: UHD 25.00p Filter Diameter: 67 mm ND Filter: 4 Positions (OFF, 1/4, 1/16, 1/64) Shortest Shooting Distance (M.O.D.): Approx. 1.0 m from the front lens	XLR Input:		XLR (3-pin) x 2 (INPUT1, INPUT2) high impedance, LINE/MIC/MIC+48V (switchable SW) LINE: +4 dBu/0 dBu (switchable menu) MIC: -40 dBu/-50 dBu/-60 dBu (switchable menu)			
Gain Setting:	L/M/H selector switch (toggle switch) Standard mode: 0 dB to 30 dB (Adjustable in 1 dB steps) (Automatic setting can be assigned to L/M/H) Extended ON: -3 dB to 30 dB (Adjustable in 1 dB steps) (Automatic setting can be assigned to L/M/H) 33 dB and 36 dB switched (when assigning [S.GAIN] to the USER button)	Audio Output		HDMI: 2 ch (LPCM)			
Color Temperature Setting:	ATW, ATW LOCK, Ach, Bch, preset 3200 K/preset 5600 K/VAR (2000 K to 15000 K)	Camera Remote:		2.5 mm diameter super mini jack x1 (ZOOM, S/S) 3.5 mm diameter mini jack x1 (FOCUS, IRIS)			
Shutter Speed:	50i/50p mode: 1/50 sec., 1/60 sec., 1/100 sec., 1/125 sec., 1/180 sec., 1/250 sec., 1/350 sec., 1/500 sec., 1/750 sec., 1/1000 sec., 1/1500 sec., 1/2000 sec., 1/3000 sec., 1/4000 sec., 1/8000 sec. 25p mode: 1/25 sec., 1/50 sec., 1/60 sec., 1/100 sec., 1/125 sec., 1/180 sec., 1/250 sec., 1/350 sec., 1/500 sec., 1/750 sec., 1/1000 sec., 1/1500 sec., 1/2000 sec., 1/3000 sec., 1/4000 sec., 1/8000 sec.	USB 3.0 HOST:		Standard-A connector, 9-pin, external media device connection*2, bus power supported			
Shutter Speed: (Slow Shutter)	50i/50p mode: 1/2 sec., 1/3 sec., 1/6 sec., 1/12 sec., 1/25 sec. 25p mode: 1/2 sec., 1/3 sec., 1/6 sec., 1/12 sec.	USB 3.0 DEVICE:		Micro-B connector, 10-pin, Mass storage function (read only)			
VFR Recording Frame Rate:	25p mode: 2, 12, 21, 23, 25, 27, 30, 37, 50 (fps)	DC IN 12V:		DC 12 V (11.4 V to 12.6 V) EIAJ Type4			
Minimum Subject Illumination:	1.1 lx (F2.8, Super Gain 36dB, Manual slow shutter 1/25s)	<b>Monitor/Viewfinder</b>		LCD Monitor: 3.5-type LCD monitor, Approx. 1,150,000 dots Viewfinder: 0.24-type EVF, Approx. 1,560,000 dots equivalent			
Digital Zoom:	2x/5x/10x, i.Zoom: max. 25x (optical zoom + digital zoom)	<b>Included Accessories</b>		Battery (AG-VBR59), Battery charger (AG-BRD50), AC adaptor, Microphone holder, Screw for microphone holder (12 mm), AC cable x 2, Eye cup, Lens hood, INPUT terminal cap, Operating instructions			
Lens Hood:	Hood with lens cover	*1: An SD memory card with a capacity of UHS Speed Class 3 (U3) is required to shoot videos with a bit rate of 100 Mbps or higher.		*2: External media devices with a capacity of below 32 GB or a capacity above 2 TB cannot be used.			
<b>Memory Card Recorder</b>		Recording Media:*1		SDHC memory card (4 GB to 32 GB), SDXC memory card (48 GB to 128 GB) UHS-I supported			
Recording Slot:	Slot x 2	Recording Slot:		Slot x 2			

## Recording Time

Recording Format		4 GB	8 GB	16 GB	32 GB	64 GB	128 GB
MOV/ MP4	UHD 100 Mbps	—	—	Approx. 20 min.	Approx. 40 min.	Approx. 1 hour 20 min.	Approx. 2 hours 40 min.
	FHD 50 Mbps	Approx. 10 min.	Approx. 20 min.	Approx. 40 min.	Approx. 1 hour 20 min.	Approx. 2 hours 40 min.	Approx. 5 hours 20 min.
AVCHD	PS 25 Mbps	Approx. 19 min.	Approx. 40 min.	Approx. 1 hour 20 min.	Approx. 2 hours 40 min.	Approx. 5 hours 20 min.	Approx. 11 hours
	PH 21 Mbps	Approx. 21 min.	Approx. 45 min.	Approx. 1 hour 30 min.	Approx. 3 hours	Approx. 6 hours	Approx. 12 hours 30 min.
	HA 17 Mbps	Approx. 30 min.	Approx. 1 hour	Approx. 2 hours	Approx. 4 hours 10 min.	Approx. 8 hours 30 min.	Approx. 17 hours
	HE 5 Mbps	Approx. 1 hour 30 min.	Approx. 3 hours 20 min.	Approx. 6 hours 40 min.	Approx. 13 hours 40 min.	Approx. 27 hours 30 min.	Approx. 56 hours
	HE 8 Mbps	Approx. 1 hour	Approx. 2 hours	Approx. 4 hours 15 min.	Approx. 8 hours 30 min.	Approx. 17 hours 10 min.	Approx. 35 hours
SA 9 Mbps	Approx. 1 hour	Approx. 2 hours	Approx. 4 hours	Approx. 8 hours	Approx. 16 hours 30 min.	Approx. 34 hours	

Please refer to the latest Non-linear Compatibility Information, Download and Service Information, etc. at the following Panasonic website:



<http://pro-av.panasonic.net/>

\*AVCHD and the AVCHD logo are registered trademarks of Sony Corporation and Panasonic Corporation. Dolby and the double-D symbols are trademarks of Dolby Laboratories. HDMI and the HDMI logo and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing, LLC. SD Logo is a trademark. SDXC/SDHC and SDHC logo marks are the registered trademarks. Quick Time is trademarks of Apple Inc., registered in the U.S. and other countries.

\*Specifications are subject to change without notice.

# Panasonic®

## [Countries and Regions]

**Panasonic Corporation**  
**AVC Networks Company**  
 1-15 Matsuo-cho, Kadoma, Osaka 571-8504  
 Japan  
<http://pro-av.panasonic.net/>

Argentina	+54 11 4122 7200	Malaysia	+60 3 7809 7888
Australia	+61 (0) 2 9491 7400	Mexico	+52 55 5488 1000
Brazil	+55 11 3889 4035	Mongolia	+976 70115577
Canada	+1 905 624 5010	Netherlands, Belgium	+31 73 640 2729
China	+86 10 6515 8828	New Zealand	+64 9 272 0100
Hong Kong	+852 2313 0888	Norway	+47 67 91 78 00
Czech Republic	+421 (0) 903 447 757	Pakistan	+92 21 111 567 111
Denmark	+45 43 20 08 57	Palestine	+972 2 2988750
Egypt	+20 2 23938151	Panama	+507 229 2955
Finland, Latvia, Lithuania, Estonia	+358 (9) 521 52 53	Philippines	+65 6277 7284
France	+33 (0) 1 47 91 64 00	Poland	+48 (22) 338 1100
Germany, Austria, Switzerland	+49 (0) 6103 313887	Portugal	+351 21 425 77 04
Greece	+30 210 96 92 300	Romania, Albania, Bulgaria, Macedonia	+40 (0) 729 164 387
Hungary	+36 (1) 382 60 60	Russia & CIS	+7 495 9804206
India	+91 1860 425 1860	Saudi Arabia	+966 (1) 4790499
Indonesia	+65 6277 7284	Singapore	+65 6277 7284
Iran (Vida)	+98 21 2271463	Slovak Republic, Croatia, Serbia, Bosnia, Montenegro, Slovenia	+421 (0) 903 447 757
(Panasonic Office)	+98 2188791102	South Africa	+27 11 3131622
Italy	+39 02 6788 367	Spain	+34 (93) 425 93 00
Jordan	+962 6 5859801	Sweden	+46 (8) 680 26 41
Kazakhstan	+7 727 298 0891	Taiwan	+886 2 2227 6214
Korea	+82 2 2106 6641	Thailand	+662 731 8888
Kuwait	+96 522431385	Turkey	+90 216 578 3700
Lebanon	+96 11665557		

U.A.E. (for All Middle East)  
 +971 4 8862142  
 Ukraine  
 +380 44 4903437  
 U.K.  
 +44(0)1344 70 69 13  
 U.S.A.  
 +1 877 803 8492  
 Vietnam  
 +65 6277 7284



JQA-0443



Factories of AVC Networks Company have received ISO14001:2004-the Environmental Management System certification. (Except for 3rd party's peripherals.)